





# **Printer Specifications**

Printer		
Print Area:	Edge-to-Edge/ Ribbon Saver	
Resolution:	300dpi	
Monochrome:	5 Sec./ Card (Up to 720 Cards/ Hour)	
YMCKO:	22 Sec./ Card	
Input Hopper:	100 Cards	
Output Hopper:	40 Cards	
Card Feeding:	Automatic Front Load/ Unload with Single By- Pass Slot	
Memory:	64MB RAM	
Display:	2 Line LCD	
Control Panel:	2 LED Buttons	
Supported Platforms:	Microsoft Windows 2000/ 2003/ XP/ Vista/ 7/ 8, Mac OS, Linux, AS/400, Open Card Format	
Communication:	Ethernet/ USB	
Power Supply:	AC110.220V, 50~60Hz	
Power Consumption:	(MAX) 48W	

### Media

Print Type:	Monochrome - Up to 2,600 Cards/ Roll
Card Size:	ISO CR-80 (54mm x 86mm/ 2.12" x 3.38")
Card Thickness:	0.38mm (15mil)~ 1.0mm (40mil)
Card Time:	DVC PFT Composite DVC

#### Printer Options

Magnetic:	ISO 7811 (Track I, II, III Read/Write), HiCo/LoCo,JIS II
Contact:	ISO 7816 (ID-1)
Contactless:	MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, iCLASS
Printer Additions:	Flipper, Laminator

## Dimensions

(W x L x H) Inch:	6.7 x 16.5 x 7.7
Weight (lbs)	10 lbs



#### Monochrome Ribbons







## Authorized Dealer



For Product Information Contact:

Card Solutions, Inc · 1209 Chicago Rd. · Troy, MI 48083 Phone: 888-252-2354 · Fax: 888-380-3777 · www.cardsolutions.biz